ROPE/CHAIN COMBINATION GYPSIES (Please see below for ordering details)

Atlantic/Storm Series	BBB			High Test (ISO only)				
	5/16"	3/8"	1/2"	1/4"	5/16"	3/8"	7/16"	1/2"
600				MPA0600117SS				
850/1250/2200	MPA0850080	MPA0850099SS		MPA0850113	MPA0850080	MPA0850112		
1000/1200	MPA1000080	MPA0850099SS		MPA1000113	MPA1000080	MPA1000112		
2500/3500/4000	MPA2500057	MPA2500061	MPA2500051 (chain only)		MPA2500057	MPA2500060	MPA2500131	MPA2500052
2500/3500/4000 MORS	MPA4000057	MPA4000061	MPA4000051 (chain only)		MPA4000057	MPA4000060	MPA4000131	MPA4000052
650H	MPA1000080	MPA1000099		MPA1000113	MPA1000080	MPA1000112		

Compact Series	BBB			High Test (ISO only)				
	5/16"	3/8"	1/2"	1/4"	5/16"	3/8"	7/16"	1/2"
Compact H600				MPH0600117				
Compact H700				MPH0700117				
Neptune - Cougar/HR1200/HR1600	MPH1200080	MPH1200099		MPH1200113	MPH1200133	MPH1200112		
Hercules	MPM1200080	MPM1200099		MPM1200113	MPM1200080	MPM1200112		
Cheetah/HR2500	MPH1200080	MPH1200099			MPH1200133	MPH1200112	MPH2500131 (no RCMS	
Jaguar/HR3500	MPH2500080	MPH2500099			*MPH1200133	*MPH1200112	MPH2500131	MPH2500052
Thor/HR4000/HR4200	MPH3500057	MPH3500061			MPH3500057	MPH3500060	MPH3500131	MPH3500052

*Non-standard shaft required for MPH120031& MPH1200112

Ordering Notes:

1. Each Muir rope/chain gypsy accepts certain ropes sizes. These rope sizes relate to the corresponding chain size of the gypsy (detailed below).

- Gypsies for 1/4" chain accepts 1/2" 3-Strand Rope
- Gypsies for 5/16" chain accepts 1/2" or 9/16" 3-Strand Rope
- Gypsies for 3/8" chain accepts 9/16" or 5/8" 3-Strand Rope
- Gypsies for 7/16" chain accepts 5/8" 3-Strand Rope
- Gypsies for 1/2" chain accepts 3/4" 3-Strand Rope

2. The above chainwheels are designed to fit short link chain only; BBB, ISO spec, etc. to maximize the number of pockets and gripping. Chain is manufactured by many sources. It is critical to match the chain to the chainwheel, therefore please be careful when sizing. Imtra only offers short link chain, BBB and ISO Spec. Do not use NACM spec chain as these have longer links and will not work in a windlass. Non-ISO chain sizes like NACM spec or miss-matching the chain and gypsy may allow the chain to skip in or jump from the gypsy pockets.